



**Lightweight,
Micro Slim
Scissor with
True Slide-Out Deck**



1330SE

Micro Scissor Lift

- 13 ft (4 m) Platform Height
- Fits On Most Elevators With Shortest Overall Length & Low GVW
- 24 in. (60 cm) Roll-Out Deck Extension with Incremental Lock Positions
- Direct Electric Drive For Exceptional Duty Cycle
- Retractable Pothole Protection
- Driveable At Full Height
- Fully Proportional Drive & Lift Controls
- Ultra Compact Design Fits Into Small And Tight Work Areas.
- Compact Size Without Compromising Generous Work Area



Features

Work Area

Roll-out deck extension with incremental locking positions
 Standard swing gate
 Lanyard attachments (2)

Performance

Direct electric drive
 Fully proportional drive and lift controls

Power

24v 85Ah DC electric power
 Battery charge indicator

Serviceability

Lubrication-free scissor bearings
 Easy maintenance access to mechanical and electrical components in a slide-out tray

Safety

Dedicated compartment protects electrical and hydraulic components
 Emergency shut-off at platform and lower controls
 Non-skid metal deck construction
 Descent alarm
 Drive speed interlock
 Multi-axis tilt sensor
 Scissor maintenance lock
 Automatic parking brake

Other Features

Removable upper controls
 Voltage-compensating fully automatic battery charger
 Hour meter
 Machine tie downs
 Non-marking tires

Optional Features

Flashing beacon (continuous)
 Inverter
 2-Year extended warranty



1330SE	U.S	Metric
Heights		
Working Height*	19 ft.*	6 m*
Platform Height	13 ft.	4 m
Stowed Height (Top Guardrail)	76 in.	1.9 m
Stowed Height (Platform Floor)	35 in.	0.9 m
Guardrail Height	39 in.	1.0 m
Toeboard Height	6 in.	15 cm
Ground Clearance (stowed)	2.5 in.	6 cm
Ground Clearance (elevated)	0.6 in.	1.5 cm
Dimensions		
Length - Stowed (Overall)	57 in.	1.45 m
Length - Stowed (Ladder Removed)	51 in.	1.3 m
Width	30 in	76 cm
Platform Length (Extended)	75 in.	1.9 m
Platform Length (Retracted)	51 in.	1.3 m
Roll-Out Deck Length	24 in.	0.6 m
Platform Width (Outside)	27.5 in.	0.7 m
Wheelbase	41 in.	1.0 m
Total Lift Capacity	530 lb	240 kg
Personnel Capacity	2	
Roll-Out Deck Capacity	250 lbs	113 kg
Speed		
Drive Speed (Stowed)	2.5 mph	4.0 km/h
Drive Speed (Elevated)	0.7 mph	1.1 km/h
Performance		
Gradeability	25%	
Turning Radius (Inside)	18 in.	45 cm
Weight (Approximately)	1,900 lbs.	860 kg
Power Source	24 v DC, 85Ah battery pack	
Controls	Proportional drive and lift controls	
Tires	9 in.	230 mm

*Metric equivalent of working height adds 2m to platform height. U.S. adds 6 ft. to platform height.
 Weight may change with certain options or configurations.

Important - MEC scissor lifts must be on a firm level surface while elevated.

Warranty - MEC Aerial Work Platforms carry a one (1) year warranty on defective component parts and a five (5) year warranty on defective structural parts. This warranty applies to the original owner only. Consult your MEC dealer for warranty details.

Distributed by:

Meets or exceeds the requirements of ANSI A92.6-2006.

Specifications subject to change without notice. Photos and diagrams in this brochure are for illustrative purposes only. Contact your MEC distributor for detailed instructions on the proper use and maintenance of this equipment.

MEC Aerial Work Platforms

1401 S. Madera Avenue
 Kerman, CA 93630 | USA
 Toll free: 1.877.MEC LIFT
 1.877.632.5438
 Tel: 559.842.1500
 Fax: 559.842.1520
 Email: info@MECawp.com | www.MECawp.com
 97010

